



Essential SmartBright G3 LED Floodlight

BVP150 LED25/NW 220-240V 30W SWB CE

2550 lm - 30 W - 4000 K

The Essential SmartBright G3 LED floodlight comes with a compact and sturdy design. Its light weight with robust die-cast aluminium housing and corrosion-proof coating is suitable for general outdoor use. More efficient than the last generation, achieves more energy-savings.

Product data

General Information		Serviceability class	
Lamp colour code	840 neutral white	Serviceability class	Class C, luminaire without serviceable parts, not serviceable
Light source replaceable	No	Light Technical	
Driver included	Yes	Standard tilt angle post-top	-
Optical cover/lens type	GB [Glass bowl/cover]	Standard tilt angle side entry	-
Luminaire light beam spread	110°	Operating and Electrical	
Control interface	-	Input Voltage	220 to 240 V
Connection	Flying leads/wires	Input frequency	50 to 60 Hz
Cable	Cable 0.3 m without plug	Inrush current	1 A
Protection class IEC	Safety class I (I)	Inrush time	0.0111 ms
Flammability mark	F [For mounting on normally flammable surfaces]	Power factor (min.)	0.9
CE mark	CE mark	Controls and Dimming	
Optic type outdoor	Symmetrical wide beam	Dimmable	No
Constant light output	No		
Number of products on MCB (16 A type B)	71		
Light source engine type	LED		

Essential SmartBright G3 LED Floodlight

Mechanical and Housing	
Housing material	Aluminum die-cast
Optical cover/lens material	Glass
Fixation material	Steel
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Textured
Overall length	170 mm
Overall width	130 mm
Overall height	29 mm
Colour	Black

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Surge protection (common/differential)	Surge protection level up to 2 kV

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	2550 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	85 lm/W
Lamp colour temperature	4000 K


Colour Rendering Index	>80
Initial chromaticity	SDCM<7
Initial input power	30 W
Power consumption tolerance	+/-10%

Application Conditions	
Ambient temperature range	-40 to +50 °C

Product Data	
Full product code	871016333018199
Order product name	BVP150 LED25/NW 220-240V 30W SWB CE
EAN/UPC – product	8710163330181
Order code	911401732392
Local order code	SB150LED25NW25W
SAP numerator – quantity per pack	1
Numerator – packs per outer box	16
SAP material	911401732392
SAP net weight (piece)	0.500 kg



Dimensional drawing



BVP150/161 Essential Smartbright LED

