



MASTER TL5 High Efficiency

MASTER TL5 HE 21W/865 SLV/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	G5 [G5]
Life to 50% failures preheat (nom.)	24000 h
Features	na [Not Applicable]
System description	High Efficiency
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	99 %
LSF preheat 6,000 hours rated	99 %
LSF preheat 8,000 hours rated	99 %
LSF preheat 16,000 hours rated	97 %
LSF preheat 20,000 hours rated	84 %

Light Technical	
Colour Code	865 [CCT of 6,500 K]
Lamp Luminous Flux 25°C EL (Nom)	1950 lm
Lamp Luminous Flux (Nom)	1725 lm
Colour Designation	Cool Daylight
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	94 lm/W
Colour Temperature, horizontal (Nom)	6500 K

Lamp Luminous Efficacy EM (Nom)	84 lm/W
Colour Rendering Index,horiz (Max)	85
Colour Rendering Index,horiz (Min)	80
Colour Rendering Index,horiz (Nom)	82
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %

Operating and Electrical	
Power (Rated) (Nom)	20.6 W
Lamp current (nom.)	0.165 A

Temperature	
Design temperature (nom.)	35 °C

MASTER TL5 High Efficiency

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Cap-base information	Green Plate
----------------------	-------------

Approval and Application

Energy efficiency label (EEL)	A+
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	23 kWh

Product Data

Full product code	871150071011655
-------------------	-----------------

Order product name	MASTER TL5 HE 21W/865 SLV/40
EAN/UPC – product	8711500710116
Order code	927926286555
Local order code	TL521W865HE
SAP numerator – quantity per pack	1
Numerator – packs per outer box	40
SAP material	927926286555
SAP net weight (piece)	79.200 g
ILCOS code	FDH-21/65/1B-L/P-G5-16/850


Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 21W/865 SLV/40	17 mm	849.0 mm	856.1 mm	853.7 mm	863.2 mm

TL5 21W/865/GP HE

Photometric data



Lightcolour /865



Lightcolour /865

MASTER TL5 High Efficiency

Lifetime



LDLE_TL5-HE8_0001-Life expectancy diagram

LDLE_TL5-HE8_0002-Life expectancy diagram



LDLM_TL5-HE8_0001-Lumen maintenance diagram

