



TORNADO

TORNADO 15W CDL B22 220-240V 1PF/6

The Helix range is a twist-shape compact fluorescent lamp, with optimal light distribution. It is available in 11W, 15W, 20W and 23W (25W), with lumen equivalence of 60W, 75W, 100W and 125W incandescent light bulb. It is also available in two color temperatures: warm white (2700K) and cool daylight (6500K). It is available in both 220-240V and 120-127V and able to operate under a wide voltage range (Power supply fluctuation). It consumes up to 80% less energy than the incandescent light bulb and lasts for 3 years.

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

General Information			
Cap base	B22 [B22]	Chromaticity coordinate Y (nom.)	337
Nominal lifetime (nom.)	8000 h	Colour Temperature, horizontal (Nom)	6500 K
Switching cycle	5,000X	Lamp Luminous Efficacy EM (Nom)	61 lm/W
		Colour Rendering Index, horiz (Nom)	80
		LLMF at end of nominal lifetime (nom.)	70 %
Light Technical		Operating and Electrical	
Colour Code	865 [CCT of 6,500 K]	Input frequency	50 or 60 Hz
Lamp Luminous Flux 25°C EL (Nom)	900 lm	Power (Rated) (Nom)	15 W
Lamp Luminous Flux (Nom)	900 lm	Lamp current (nom.)	110 mA
Colour Designation	Cool Daylight	Starting time (nom.)	0.3 s
Lumen maintenance 2,000 hours (nom.)	85 %	Warm-up time to 60% light (min.)	5 s
Lumen maintenance 5,000 hours (nom.)	75 %	Warm-up time to 60% light (max.)	60 s
Chromaticity coordinate X (nom.)	313		

TORNADO

Power factor (nom.)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	No
Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.5 mg
Energy consumption kWh/1,000 hours	15 kWh

Product Data	
Full product code	871829113801300
Order product name	TORNADO 15W CDL B22 220-240V 1PF/6
EAN/UPC – product	8718291138013
Order code	929689858202
SAP numerator – quantity per pack	1
Numerator – packs per outer box	6
SAP material	929689858202
SAP net weight (piece)	0.054 kg

Dimensional drawing



Product	D (max)	C (max)	F (max)
TORNADO 15W CDL B22 220-240V 1PF/6	51.5 mm	106.0 mm	42.5 mm

QSPIR-F 15W/865 B22 220-240V 50/60Hz

