



MASTER LEDcandles – Eye-catching design for chandeliers and other decorative fixtures

MASTER LEDcandle DiamondSpark

Delivering incandescent-like sparkling light effects, MASTER LEDcandle bulbs are ideal for general and decorative lighting in the hospitality industry, as well as in home environments. The dimmable MASTER LEDcandles drive further efficiencies, while helping to create the desired atmosphere. Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass bulbs fit all existing fixtures with an E14 and B15 socket. Drawing upon inputs from chandelier makers and designed to enhance the aesthetic appeal of the chandelier or luminaire, not only when lit but also when not, these lamps come in a classical slender shape with a unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimizes maintenance cost. The flame-shaped candle lamps comes in a classical slender shape with a unique, eye-catching lens design that perfectly complements modern LED candles.

Benefits

- Sparkling warm white light
- Up to 80% energy saving
- Lower maintenance costs

MASTER LEDcandle DiamondSpark

Features

- Retrofittable with existing E14 and B22 holders
- Lifetime of 20,000 hours
- Unique DiamondSpark lens
- Free of mercury and hazardous materials


Application

- Hotels, restaurants, bars, cafés
- Chandelier or modern luminaire

Versions



Dimensional drawing



Product	D	C
MASTER LEDlustre DT 6-40W E14 P48 CL	48 mm	95 mm

Product	D	C
MASTER LEDcandle DT 6-40W E14 B38 CL_AP	38 mm	113 mm

MASTER LEDcandle DiamondSpark

Dimensional drawing

1.2 D



Product	D	C
MASTER LEDlustre DT 6-40W E27 P48 CL	48 mm	93 mm

Product	D	C
MASTER LEDcandle DT 6-40W B22 B38 CL	38 mm	111 mm

MASTER LEDcandle DiamondSpark

Approval and Application

Energy Consumption kWh/1000 h	6 kWh
Energy Efficiency Label (EEL)	A+

Controls and Dimming

Dimmable	Yes
----------	-----

Operating and Electrical

Input Frequency	50 to 60 Hz
Voltage (Nom)	220-240 V
Wattage Equivalent	40 W
Power (Rated) (Nom)	6 W
Starting Time (Nom)	0.5 s

General Information

Nominal Lifetime (Nom)	25000 h
Switching Cycle	50,000X

Light Technical

Colour Code	822-827
Correlated Colour Temperature (Nom)	- K
Colour Rendering Index (Nom)	80
Llmf At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux (Nom)	470 lm

Mechanical and Housing

Bulb Finish	Clear
-------------	-------

Temperature

T-Case Maximum (Nom)	95 °C
----------------------	-------

General Information

Order Code	Full Product Name	Cap-Base
929001140408	MASTER LEDcandle DT 6-40W E14 B38 CL_AP	E14
929001140602	MASTER LEDlustre DT 6-40W E14 P48 CL	E14
929001140702	MASTER LEDlustre DT 6-40W E27 P48 CL	E27
929001140802	MASTER LEDcandle DT 6-40W B22 B38 CL	B22

Mechanical and Housing

Order Code	Full Product Name	Bulb Shape
929001140408	MASTER LEDcandle DT 6-40W E14 B38 CL_AP	B38
929001140602	MASTER LEDlustre DT 6-40W E14 P48 CL	P48
929001140702	MASTER LEDlustre DT 6-40W E27 P48 CL	P48
929001140802	MASTER LEDcandle DT 6-40W B22 B38 CL	B38





MASTER LEDcandle DiamondSpark

