



# Optivision – downlight performance

## OptiVision MVP507

Optivision is an asymmetric downlighting luminaire that combines compact dimensions with very high efficiency. Available with narrow, medium and wide beams for flexibility in application, it provides excellent control of spill light and limitation of glare and upward leakage of light. Optivision can accommodate metal-halide lamps for good colour rendering or high-pressure sodium lamps for economical operation. Excellent spill-light control, limitation of glare and upward leakage of light is secured by asymmetric optics that achieve peak intensity at 60° and a sharp cut-off of light at 80°. The MHN-LA/FC lamps guarantee pleasant and natural colour rendering and comfortable atmosphere.

### Benefits

- Asymmetrical downlighting luminaire combines compact dimensions with high efficiency
- Available with narrow, medium and wide beams for flexibility in use; sharp beam cut-off for excellent control of spill light and limitation of glare and upward light leakage

### Features

- Compact dimensions
- High efficiency
- Can be used with metal-halide lamps or high-pressure sodium lamps
- Choice of narrow, medium and wide beams

### Application

- Sports facilities
- Industrial areas
- Car parks

# OptiVision MVP507

## Specifications

<b>Type</b>	MVP507
<b>Light source</b>	HID: - 1 x MASTER MHN-FC / XW / 1000, 2000 W - 1 x MASTER MHN-LA / XWH / 1000, 2000 W - 1 x MASTER HPI-T Plus / E40 / 1000 W - 1 x MASTER SON-T PIA / E40 / 600 W - 1 x SON-T / E40 / 600, 1000 W
<b>Lamp included</b>	Yes (K or light color 643, 740, 842 or 956) No
<b>Optic</b>	Narrow beam (NB) Medium beam (MB) Wide beam (WB)
<b>Ignitor</b>	Series (SI), integral Semi-parallel (SP), external on a separate gear tray (ZVF320) Parallel (PA), external on a separate gear tray (ZVF320)
<b>Materials and finishing</b>	Housing: non-corrosive, high-pressure die-cast aluminum Glass: thermally hardened, 4 mm thick Mounting bracket: hot-dipped galvanized steel Clips and hinges: stainless steel Reflector: high-reflectivity and high-purity anodized aluminum Finishing in raw aluminum

<b>Installation</b>	On mast headframe, ceiling and wall mounting Protractor scale integrated for aiming Ambient temperature outdoor: 35°C Drag factor (Cx): 0.447 Projected area in horizontal position: 0.127 m Max adjustment from the horizontal: -10 / +10°, downlighting only
<b>Maintenance</b>	Lamp access by opening the hinged front glass for in-position lamp replacement Built-in safety switch to cut off current while opening the luminaire, only in MHN-LA lamp versions No internal cleaning required
<b>Accessories</b>	Simple aiming device (ZVP507 SAD)
<b>Remarks</b>	Equipped with aluminum connection box with ignitor, installed on a separate gear tray (ZVF320) Bracket can be inverted to allow mounting above or below a cross arm Specially designed heat fins Pre-wired external 220 - 240 V / 50 Hz or 380 - 415 V / 50 Hz gear trays are available, to be ordered separately
<b>Main applications</b>	Sports, car parks, industrial areas

## Versions



OptiVision MVP507, světlomet pro sportoviště a plošné osvětlení

## Product details



# OptiVision MVP507

## Approval and Application

Mech. impact protection code	IK08
------------------------------	------

## General Information

Ball impact resistance mark	Ball Impact Resistance mark
CE mark	CE mark
Light source colour	842 neutral white
Lamp family code	MHN-LA
Number of light sources	1
Product Family Code	MVP507

## Mechanical and Housing

Colour	Aluminium
--------	-----------

## General Information

Order Code	Full Product Name	Lamp power	Optic type
910403025412	MVP507 MHN-LA1000W/842 230V WB SI	1000 W	Wide beam
910403787412	MVP507 MHN-LA2000W/842 400V WB SI SL	2000 W	Wide beam
910403787512	MVP507 MHN-LA2000W/842 400V MB SI SL	2000 W	Medium beam

